KIP540(-S), KIP542(-S), KIP546(-S), KIP547(-S), KIP555(-S)

Display size
40", 42", 46",
47" or 55"

LB (KG)

Max load **75lb (34kg)**

Portrait Kiosk Enclosure

Fits 40", 42", 46", 47", and 55" Displays up to 4" (101mm) Thick

Make a statement with Peerless-AV's versatile digital signage kiosk. Designed to support ultra-thin or thicker commercial displays, this kiosk accentuates the sleek look of the display while providing ample space to integrate a media player, interactive touch system, etc, to create a complete interactive kiosk experience. Paired with a wide range of aesthetic options, this modular line of kiosks makes it easy to execute any advertising or branding strategy.

Displaying digital signage content has never been easier!

Additional Features

- Eight point adjustment to quickly position the display within the kiosk window for a flush alignment
- Accommodates ultra-thin or deeper commercial displays up to 4" (101mm) thick, while accentuating slim kiosk design
- ✓ VESA® 200 x 200 up to 800 x 400mm compatible
- Thermostat controlled circulation fans ensure proper airflow within the kiosk
- Secured doors allow convenient access to the display, media player and other internal components for easy installation and maintenance
- Stand-alone kiosk enclosure or fully integrated with display, media player, power and thermal management, etc.
- Supports a wide range of aesthetic options including glass/acrylic, multiple colors, vinyl wraps, etc. to best match environment or promote brand strategy
- Pre-assembled to simplify installation of entire solution





Fits most 40", 42", 46", 47" and 55" displays up to 4" (101mm) thick

KIP540(-S) Portrait Kiosk Enclosure fits 40" Displays up to 4" (101mm) Thick KIP542(-S) Portrait Kiosk Enclosure fits 42" Displays up to 4" (101mm) Thick KIP546(-S) Portrait Kiosk Enclosure fits 46" Displays up to 4" (101mm) Thick KIP547(-S) Portrait Kiosk Enclosure fits 47" Displays up to 4" (101mm) Thick KIP555(-S) Portrait Kiosk Enclosure fits 55" Displays up to 4" (101mm) Thick
--

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS	
KIP540/KIP542(-S) KIP546/ KIP547(-S) KIP555(-S)	28.00" x 72.12" x 20.50" (711 x 1832 x 521mm) 34.00" x 72.12" x 20.50" (864 x 1832 x 521mm) 34.00" x 78.12" x 20.50" (864 x 1984 x 521mm)	165lb (75kg) 181lb (82kg) 196lb (89kg)	75lb (34kg)	Powder Coat	KIP540-S, KIP542-S,	Gloss black Silver

Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
KIP540/KIP542(-S) KIP546/ KIP547(-S) KIP555(-S)	48.00" x 78.00" x 40.00" (1219 x 1966 x 1016mm) 48.00" x 78.00" x 40.00" (1219 x 1966 x 1016mm) 48.00" x 83.00" x 40.00" (1219 x 2108 x 1016mm)	212lb (96kg) 228lb (103kg) 244lb (111kg)	KIP540: 735029297314 KIP540-S: 735029297321 KIP542: 735029297338 KIP542-S: 735029297345 KIP546: 735029296737 KIP546-S: 735029296775 KIP547: 735029296744 KIP547-S: 735029296782 KIP555: 735029296751 KIP555-S: 735029296805	Kiosk with display mounting hardware	1

Accessories PVP1000-PL6: Surge Protector with Six Outlets

Agion antimicrobial protection:

Agion® antimicrobial* finish available to assist in controlling the spread of infections. Contact Peerless-AV Customer Care for more information.

*Antimicrobial protection is limited to the treated article and does not protect a user against disease causing bacteria. Always clean products thoroughly after each use.


CL-SCG200: Screen Cleaning Gel

DEB-HD10: 32' (10m) High Speed HDMI® Cables with Ethernet

KioskBuilder™:

Build your own Integrated Kiosk @ kiosks.peerless-av.com including integration services, flat panel display, media player, content management software, power protection, thermal management, display protection, vinyl graphics, etc.

All dimensions = inch (mm)



MODEL NO.	DIMENSION "A"	DIMENSION "B"	DIMENSION "C"	DIMENSION "D"	DIMENSION "E"	DIMENSION "F"	DIMENSION "G"
KIP540	34.97"(888mm)	19.67"(500mm)	6.80"(173 mm)	. <mark>38</mark> "(10mm)	28.00"(711mm)	72.12"(1832mm)	20.50" (521mm)
KIP542	36.72"(933mm)	20.65"(525mm)	6.80"(173 mm)	. <mark>38</mark> "(10mm)	28.00"(711mm)	72.12"(1832mm)	20.50" (521mm)
KIP546	40.20"(1021mm)	22.61"(574mm)	6.80"(173 mm)	. <mark>38</mark> "(10mm)	34.00"(864mm)	72.12"(1832mm)	20.50"(521mm)
KIP547	41.07"(1043mm)	23.10"(587mm)	6.80"(173 mm)	.38"(10mm)	34.00"(864mm)	72.12"(1832mm)	20.50" (521mm)
KIP555	48.05"(1220mm)	27.03"(686mm)	6.80"(173 mm)	.38"(10mm)	34.00"(864mm)	78.12"(1984mm)	20.50"(521mm)

Architect Specifications

The Portrait Kiosk Enclosure shall be a Peerless-AV model KIP540(-S), KIP542(-S), KIP546(-S), KIP547(-S) or KIP555(-S) and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV

2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500

Peerless-AV Europe

Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom

+44 (0) 1923 200100 Fax: +44 (0) 1923 200101

Peerless-AV de México

Ave de las Industrias 413 Parque Industrial Escobedo Escobedo, N.L., Mexico 66050

+52 (81) 8384-8300 Fax: +52 (81) 8384-8360

