

FPE42F(H)-EU/UK-S  
 FPE47F(H)-EU/UK-S  
 FPE55F(H)-EU/UK-S



Display size  
**40"-55"**



Max load  
**250lb (113kg)**

# Indoor/Outdoor Protective Enclosures

FOR 40" TO 55" DISPLAYS


Peerless-AV's display enclosures help create worry-free digital signage. The steel and corrosion resistant enclosures protect the screen from outdoor elements, pollution, theft and vandalism. The enclosures also include built-in tubular keyed compression locks for added security. Peerless-AV's Indoor/Outdoor Protective Enclosures are waterproof and sealed with a rubber gasket, so your enclosure can withstand the elements in any climate. All enclosures are available with a heated or fan-cooled option, and thermostat controlled fans and heat help ensure the display will continue to function in most outdoor conditions.



*Peerless-AV's Indoor/Outdoor Protective Enclosures offer easy screen access, making screen installation and maintenance a breeze.*

## Additional Features

- ✓ Triple corrosion protection with galvanized cold rolled steel, zinc powder primer & powder paint
- ✓ Available in fan cooled or heated model options with thermostat controlled fans to ensure proper air circulation and heat ventilation
- ✓ Shatter-proof tempered glass window
- ✓ Incremental depth adjustment allows for ideal display placement of 1/2" from interior window
- ✓ Tested to IP 56 standards
- ✓ Fits displays with mounting hole patterns 730 x 405mm (28.75"W x 15.95"H)



**EASY SCREEN ACCESS**  
 Gas struts deliver easy access to screen for installation and maintenance

**COMPONENT POWER**  
 6 outlet 115V 15A power strip provides power to internal components

**CIRCULATION FANS**  
 Ensure proper air flow within the unit

**RUBBER GASKET SEAL**  
 Protects from ingress of water and other harmful elements

**UNIVERSAL COMPATIBILITY**  
 Unit includes Peerless-AV's universal display mount PF660 that accommodates displays with up to 600 x 400mm VESA® mounting pattern



Closed view



Thermostat controls



Stainless steel key lock



**RoHS**

**MADE IN USA**

## Model Numbers

<b>FPE42F-EU/UK-S:</b>	Indoor/Outdoor Protective Enclosure with Cooling Fans for 40"-42" Displays
<b>FPE47F-EU/UK-S:</b>	Indoor/Outdoor Protective Enclosure with Cooling Fans for 46"-47" Displays
<b>FPE55F-EU/UK-S:</b>	Indoor/Outdoor Protective Enclosure with Cooling Fans for 52"-55" Displays
<b>FPE42FH-EU/UK-S:</b>	Indoor/Outdoor Protective Enclosure with Cooling Fans and Thermostat Controlled Heater for 40"-42" Displays
<b>FPE47FH-EU/UK-S:</b>	Indoor/Outdoor Protective Enclosure with Cooling Fans and Thermostat Controlled Heater for 46"-47" Displays
<b>FPE55FH-EU/UK-S:</b>	Indoor/Outdoor Protective Enclosure with Cooling Fans and Thermostat Controlled Heater for 52"-55" Displays

## Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
<b>FPE42F(H)-EU/UK-S</b>	51.41" x 33.80" x 11.68" (1306 x 859 x 297mm)	150lb (68kg)	250lb (113kg) PF660: 200lb (91kg)	Zinc powder primer and a scratch resistant gray powder paint	Stone gray
<b>FPE47F(H)-EU/UK-S</b>	55.76" x 36.25" x 11.68" (1416 x 921 x 297mm)	160lb (73kg)			
<b>FPE55F(H)-EU/UK-S</b>	62.74" x 40.18" x 11.68" (1594 x 1021 x 297mm)	170lb (77kg)			

AMBIENT TEMPERATURE RANGE	COOLING FAN OPERATING TEMPERATURE	HEATER OPERATING TEMPERATURES	AVAILABLE POWER LOAD WATTAGE
Non-Heated 41 to 95° F (5 to 35° C) Heated -35 to 95° F (-37 to 35° C)	Factory set by Peerless to turn on at 70° F (21° C)	Turns on at 40° ±7° F (4° ±7° C) Turns off at 60° ±5° F (15° ±5° C)	Fan cooled (1550 WATTS) Heated (700 WATTS)

**NOTE:**  
Customizable enclosures and mounts available. Call tech support for further details. IR remotes controls may be blocked depending on placement of sensor on certain displays.


*Due to solar loading, the enclosure should not be used in direct sunlight without a high temperature display or the display may go isotropic.*

## Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE		PACKAGE CONTENTS	UNITS IN PACKAGE
			EU models	UK models		
<b>FPE42F-EU/UK-S</b>	52.5" x 36.25" x 12" (1334 x 921 x 305mm)	150lb (68kg)	735029290650	735029292067	Complete enclosure assembly, Peerless-AV PF660 mount, 6 outlet power strip, Roxtec cable seals, wood mounting hardware, locks and key	1
<b>FPE47F-EU/UK-S</b>	57" x 38" x 12" (1448 x 965 x 305mm)	160lb (73kg)	735029292098	735029292104		
<b>FPE55F-EU/UK-S</b>	64" x 42.5" x 12" (1626 x 1080 x 305mm)	170lb (77kg)	735029292128	735029292135		
<b>FPE42FH-EU/UK-S</b>	52.5" x 36.25" x 12" (1334 x 921 x 305mm)	155lb (70kg)	735029292074	735029292081		
<b>FPE47FH-EU/UK-S</b>	57" x 38" x 12" (1448 x 965 x 305mm)	165lb (75kg)	735029290100	735029292111		
<b>FPE55FH-EU/UK-S</b>	64" x 42.5" x 12" (1626 x 1080 x 305mm)	175lb (79kg)	735029291480	735029292142		

## Accessories

<b>FPEWM:</b>	Indoor/Outdoor Tilting Wall Mount for FPE42F(H)-EU/UK-S, FPE47F(H)-EU/UK-S & FPE55F(H)-EU/UK-S Protective Enclosures
<b>FPECMC models:</b>	Indoor/Outdoor Tilting Concrete Ceiling Mount for FPE42F(H)-EU/UK-S, FPE47F(H)-EU/UK-S & FPE55F(H)-EU/UK-S Protective Enclosures
<b>FPECM I models:</b>	Indoor/Outdoor Tilting I-Beam Mount for FPE42F(H)-EU/UK-S, FPE47F(H)-EU/UK-S & FPE55F(H)-EU/UK-S Protective Enclosures
<b>FPEPM models:</b>	Indoor/Outdoor Tilting Pedestal Mount for FPE42F(H)-EU/UK-S, FPE47F(H)-EU/UK-S & FPE55F(H)-EU/UK-S Protective Enclosures



MODEL NO.	DIMENSION "A"	DIMENSION "B"	DIMENSION "C"	DIMENSION "D"	DIMENSION "E"	DIMENSION "F"	DIMENSION "G"
FPE42F(H)-EU/UK-S	51.41" (1306mm)	33.80" (859mm)	25.09" (637mm)	42.18" (1071mm)	39.67" (1008mm)	36.50" (927mm)	21.00" (533mm)
FPE47F(H)-EU/UK-S	55.76" (1416mm)	36.25" (921mm)	26.78" (680mm)	44.65" (1134mm)	42.20" (1072mm)	41.50" (1054mm)	23.50" (597mm)
FPE55F(H)-EU/UK-S	62.74" (1594mm)	40.18" (1021mm)	30.26" (769mm)	48.51" (1232mm)	46.83" (1189mm)	48.50" (1232mm)	27.50" (699mm)

## Architect Specifications

The Peerless-AV Indoor/Outdoor Protective Enclosure shall be model FPE42F(H)-EU/UK-S, FPE47F(H)-EU/UK-S or FPE55F(H)-EU/UK-S and shall be located where indicated on the plans. It shall be constructed of heavy gauge cold rolled steel. Finished with Zinc Powder Primer and a scratch resistant ASA-70 gray protective coating. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit [peerless-av.com](http://peerless-av.com) to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

**Peerless-AV**  
2300 White Oak Circle  
Aurora, IL 60502 USA  
  
(800) 865-2112  
(630) 375-5100  
Fax: (800) 359-6500

**Peerless-AV Europe**  
Unit 3 Watford Interchange  
Colonial Way, Watford  
Herts, WD24 4WP  
United Kingdom  
+44 (0) 1923 200100  
Fax: +44 (0) 1923 200101

**Peerless-AV de México**  
Ave de las Industrias 413  
Parque Industrial Escobedo  
Escobedo, N.L.,  
Mexico 66050  
+52 (81) 8384-8300  
Fax: +52 (81) 8384-8360

